

*Maximum
Sensor Protection*



Model 43408
Gill Aspirated Radiation Shield

The Gill Aspirated Radiation Shield provides maximum sensor protection from incoming short wave solar radiation and outgoing long wave radiation.

The shield employs concentric downward facing intake tubes and a small canopy shade to isolate the sensor from direct and indirect radiation. A continuous duty blower draws ambient air through the intake tubes and across the sensor minimizing heat transfer to the sensor. Compact shield components reduce radiation-absorption and improve aspiration efficiency. Specially selected plastic materials provide high reflectivity, low conductivity, and maximum weatherability.

The versatile DC blower is designed for continuous duty of 80,000 hours at 25°C. Brushless electronic commutation is achieved using dependable solid state circuitry.



The Temperature Probe is a 1000 Ω Platinum RTD encased in a stainless steel protective sheath. The sensing element is secured in a convenient junction box that fits YOUNG radiation shields. The probe is available with various output options. The 4-20 mA current output is useful in high noise, industrial settings or for long cable lengths. The 0.1 VDC option provides a calibrated voltage output signal.

The Relative Humidity / Temperature Probe combines a high accuracy humidity sensor and a 1000 Ω Platinum RTD. Available with 0-1 VDC or 4-20 mA outputs, sensors are mounted in a common junction box.



Specifications

Sensor Types:

Accommodates temperature and humidity sensors up to 19 mm (.75 in) diameter

Radiation Error:

@ 1000 W/m² intensity
Ambient Temperature: 0.2° C (0.4° F) RMS
Delta T: 0.05° C (0.1° F) RMS with like shields equally exposed.

Aspiration Rate:

3.4 to 7.6 m/s (11 to 25 fps) depending on sensor size.

Construction:

UV stabilized thermoplastic shield, white.
Aluminum cross tube & mounting brackets, white painted.
Stainless Steel U-bolt clamp

Dimensions:

Length: 110-190 cm (43-75 in) adjustable.
Shield: 34 mm (1.3 in) dia. x 10 cm (4 in) length.
Blower Housing: 15 cm (5.9 in) dia. x 9 cm (3.5 in) length.
Mounting: Adjustable V-blocks and U-bolts fit vertical, horizontal or diagonal tower members 25-50 mm (1-2 in) dia.

Power Requirement:

12 VDC @ 500 mA for blower.
AC adapter included.

Weight:

Net weight- 2.4 kg (5.3 lb)
Shipping weight- 5.9 kg (13 lb)

MODEL 41342 Platinum Temp. Probe

Sensor Type:

1000 Ω Platinum RTD

Accuracy:

±0.3° C at 0° C(standard)
±0.1° C at 0° C(optional)

Available Outputs:

4 wire RTD(41342)
4-20 mA(41342L)
0-1 VDC(41342V)

MODEL 41372 Rel. Humidity/Temp. Probe

Sensor Type:

Temperature:1000 Ω Platinum RTD
Humidity:Capacitive Polymer

Accuracy:

Temperature:
±0.3° C at 0° C(standard)
±0.1° C at 0° C(optional)
Humidity:......3% from 0 to 100% RH

Available Outputs:

4-20 mA(41372L)
0-1 VDC(41372V)

Ordering Information

MODEL

GILL ASPIRATED RADIATION SHIELD- WITH 110V / 60 HZ AC ADAPTER	43408
GILL ASPIRATED RADIATION SHIELD- WITH 230V / 50-60 HZ AC ADAPTER	43408H
<i>Note: Standard unit supplied with blank mounting plug. Plug may be drilled to order (26 mm max.)</i>	
TEMPERATURE PROBE- RTD OUTPUT	41342
4-20 mA OUTPUT*	41342L*
0-1 VDC OUTPUT*	41342V*
RELATIVE HUMIDITY/TEMPERATURE PROBE*	
4-20 mA OUTPUT*	41372L*
0-1 VDC OUTPUT*	41372V*
*SPECIFY TEMPERATURE SCALING FOR PROBES:	
-50 to +50 C°	413***C
-50 to +150 F°	413***F
ACCESSORY JUNCTION BOX <i>Specify sensor diameter (10 mm max.)</i>	41390

